


Slewing Drive Performance Parameters	
Rated Output Speed	0,025 rpm
Rated Output Torque	6405 N.m
Tilting Moment	10 kN.m
Holding Torque	56 kN.m
Static Axial Rating	100 kN
Static Radial Rating	65 kN
Corrosion Protection	C3
Temperature	-30°C~+60°C
Gear Ratio	61 : 1
Hard Limit	±60°
Precision	≤ 0.17°
24VDC Planetary Reducer Motor Performance Data	
Gear Ratio	717:1
Rated Output Torque	300 N.m
Rated Output Speed	1.5 rpm
Rated Current	≤7.5 A
IP Class	IP 65
Temperature	-30 ~ +60°C

Wire Define:
 Pin 1 (Black) motor -
 Pin 2 (Red) motor +

REV	DATE	REVISER	REVISER		
DESIGNED BY	2019/7/28	Li Ming	 www.coresundrive.com resun Drive Equipment Changzhou Co.,Ltd.	<h1>Slewing Drive</h1>	
CHECKED BY	2019/7/28	Rui Wang			
APPROVED BY	2019/7/28	Shane Zhang			
ALL PROPRIETARY RIGHTS IN THE SUBJECT MATTER HERE OF ARE RESERVED, AND NO PERMISSION IS GRANTED OR TO DISCLOSE REPRODUCE THIS PRINT IN WHOLE OR IN PART, ANY OF THE INFORMATION TO OTHERS.			WEIGHT	SCALE	<h2>VH9-110S-RC-2415300</h2>
SYMBOLS ISO			SIZE	A3	
			SHEET	1/1	REV A